

View Online at <https://aerobasegroup.com/nsn/5305-01-348-8497>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.235 inches and 0.265 inches

**Fastener Length:**

Between 0.837 inches and 0.857 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.375 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Material Accommodated Thickness:**

Between 0.075 inches and 0.089 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 304 stand-off iron alloy 660 fastener

**Material Specification:**

Astm a581 assn standard single material response stand-off or mil-s-23195 military specification single material response stand-offams 5732 assn standard single material response fastener or ams 5731 assn standard single material response fastener

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-23195 spec.