## NSN 5305-01-349-4193

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-349-4193

view Offinite at https://aerobasegroup.com/hist//3000-01-049-4190
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.469 inches
Fastener Length:
Between 1.328 inches and 1.375 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.578 inches and 0.633 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.312 inches
Grip Length:
Between 0.865 inches and 0.885 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
220000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads
Product Name:
Navy special project
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5305-01-349-4193

Close Tolerance Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0