NSN 5305-01-349-4319

Machine Screw - Page 1 of 2

No

View Online at https://aerobasegroup.com/nsn/5305-01-349-4319



| Thread Class: |
|--|
| За |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.339 inches |
| Fastener Length: |
| Between 0.386 inches and 0.416 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.308 inches and 0.322 inches |
| Head Height: |
| Between 0.105 inches and 0.115 inches |
| Internal Drive Style: |
| Torque-set ribbed |
| Thread Diameter: |
| 0.164 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 36.0 rockwell c and 40.0 rockwell c |
| Screw Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Bearing Surface Of Head Surface Finish: |
| 32.0 microinches |
| Shank Surface Finish: |
| 32.0 microinches |
| Thread Surface Finish: |
| 32.0 microinches |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1218 professional/industrial association standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

NSN 5305-01-349-4319 Machine Screw - Page 2 of 2

Fiig: A500d0

