## NSN 5305-01-349-4320



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-349-4320 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.339 inches **Fastener Length:** Between 0.699 inches and 0.729 inches **Head Style:** Pan **Head Diameter:** Between 0.308 inches and 0.322 inches **Head Height:** Between 0.105 inches and 0.115 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Product Name:** Navy special project **Screw Material:** Titanium alloy uns r56400 **Screw Material Specification:** Ams 4967 assn standard single material response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches

Thread Series Designator:
Unjc
Specification Data:
80205-nas1218 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-349-4320

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0