NSN 5305-01-349-5262

View Online at https://aerobasegroup.com/nsn/5305-01-349-5262

Machine Screw - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.121 inches **Fastener Length:** Between 0.157 inches and 0.188 inches **Head Style:** Pan **Head Diameter:** Between 0.149 inches and 0.167 inches **Head Height:** Between 0.053 inches and 0.062 inches **Locking Feature:** Strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Screw Material:** Iron alloy 660 **Locking Feature Material:** Plastic polychlorotrifluoroethylene **Screw Material Specification:** Ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:**

32.0 microinches

NSN 5305-01-349-5262

Machine Screw - Page 2 of 2

A500d0



Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Filg: