NSN 5305-01-349-8755

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-349-8755

| Thread Class: |
|---------------------------------------------------------------------------------------------------|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.338 inches |
| Fastener Length: |
| Between 0.688 inches and 0.728 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| 0.305 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or ams 5737 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| |
| 80205-nas1973 professional/industrial association standard |

N/a

NSN 5305-01-349-8755

Close Tolerance Screw - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A003b0