NSN 5305-01-349-9131



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-349-9131 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.335 inches **Fastener Length:** Between 0.410 inches and 0.440 inches **Head Style:** Round extended washer **Head Diameter:** 0.353 inches **Head Height:** Between 0.085 inches and 0.105 inches **Extended Washer Diameter:** Between 0.167 inches and 0.190 inches **Extended Washer Thickness:** Between 0.030 inches and 0.037 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Steel comp 4340 **Screw Material Specification:** Mil-s-5000 military specification single material response **Screw Surface Treatment:** Cadmium **Screw Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas8303-7 professional/industrial association standard Shelf Life:

N/a

Unit Of Measure:

NSN 5305-01-349-9131

Machine Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5000 spec.