

View Online at <https://aerobasegroup.com/nsn/5305-01-349-9216>

**Thread Direction:**

Right-hand

**Thread Length:**

7.0 millimeters

**Fastener Length:**

Between 7.5 millimeters and 8.0 millimeters

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 3.90 millimeters and 4.40 millimeters

**Locking Feature:**

Patch

**Internal Drive Style:**

Cross recess type 1

**End Application:**

Receiver-transmitter rt-1523c/u

**Thread Diameter:**

2.2 millimeters

**Thread Pitch In Millimeters:**

0.45

**External Thread Tolerance Class:**

6g

**Countersink Angle:**

Between 90.0 degrees and 92.0 degrees

**Screw Material:**

Stainless steel

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Qq-s-763 federal specification single material response and fed-std-66 federal specification single material response

**Locking Feature Material Specification:**

L-p-410 federal specification single material response

**Bearing Surface Of Head Surface Treatment:**

Passivate

**Screw Surface Treatment:**

Passivate

**Bearing Surface Of Head Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0