

View Online at <https://aerobasegroup.com/nsn/5305-01-349-9216>

Thread Direction:

Right-hand

Thread Length:

7.0 millimeters

Fastener Length:

Between 7.5 millimeters and 8.0 millimeters

Head Style:

Flat countersunk

Head Diameter:

Between 3.90 millimeters and 4.40 millimeters

Locking Feature:

Patch

Internal Drive Style:

Cross recess type 1

End Application:

Receiver-transmitter rt-1523c/u

Thread Diameter:

2.2 millimeters

Thread Pitch In Millimeters:

0.45

External Thread Tolerance Class:

6g

Countersink Angle:

Between 90.0 degrees and 92.0 degrees

Screw Material:

Stainless steel

Locking Feature Material:

Plastic polyamide

Screw Material Specification:

Qq-s-763 federal specification single material response and fed-std-66 federal specification single material response

Locking Feature Material Specification:

L-p-410 federal specification single material response

Bearing Surface Of Head Surface Treatment:

Passivate

Screw Surface Treatment:

Passivate

Bearing Surface Of Head Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0