## NSN 5305-01-349-9566



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-349-9566 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.375 inches **Fastener Length:** 2.250 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.642 inches and 0.656 inches **Head Height:** 0.437 inches **Hole Diameter:** Between 0.061 inches and 0.067 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.437 inches Width Across Flats: Between 0.375 inches and 0.379 inches **Hole Quantity: Hole Type:** Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch

**Hole Configuration Style:** 

Round internal hexagon

Material:

Iron alloy 660

**Material Specification:** 

Ams 5731 assn standard single material response or ams 5737 assn standard single material response

**Precious Material And Location:** 

silver

## NSN 5305-01-349-9566

Socket Head Cap Screw - Page 2 of 2



Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Ams2411 assn standard single treatment response
Thread Series Designator:
Unrf
Specification Data:
80205-nas1351 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0