## NSN 5305-01-350-2275

Machine Screw - Page 1 of 2

**Thread Class:** 

Right-hand

**Thread Direction:** 

За



View Online at https://aerobasegroup.com/nsn/5305-01-350-2275

Thread Length:
0.308 inches
Fastener Length:
Between 0.344 inches and 0.375 inches
Head Style:
Pan
Head Diameter:
Between 0.149 inches and 0.167 inches
Head Height:
Between 0.053 inches and 0.062 inches
Locking Feature:
Strip
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Iron alloy 660
Locking Feature Material:
Plastic polychlorotrifluoroethylene
Screw Material Specification:
Ams 5737 assn standard single material response
Screw Surface Treatment:
Passivate
Screw Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches

## NSN 5305-01-350-2275

Machine Screw - Page 2 of 2

A500d0



Thread Series Designator:
Unjc
Specification Data:
80205-nas1190 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: