NSN 5305-01-350-2466

Fiig: A500d0



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-350-2466 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.532 inches and 0.625 inches **Fastener Length:** Between 0.594 inches and 0.625 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 60000 pounds per square inch **Screw Material:** Steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1026 or steel comp 1030 or steel comp 1116 or steel comp 1118 or steel comp 1119 or steel comp 1132 **Screw Material Specification:** Astm a29 assn standard all material responses **Screw Surface Treatment:** Zinc and chromate **Screw Surface Treatment Specification:** Astm b633, type 2 assn standard single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No