

View Online at <https://aerobasegroup.com/nsn/5305-01-350-4207>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

Between 0.572 inches and 0.619 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.339 inches and 0.381 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Shank Unthreaded Hole Diameter:

0.065 inches first hole and 0.075 inches first hole

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.190 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

220000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.376 inches first hole

Surface Finish:

32.0 microinches bearing surface of head 32.0 microinches grip 32.0 microinches threads

Product Name:

Navy special project

Material:

Nickel alloy 718

Material Specification:

Ams 5662 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0