NSN 5305-01-350-4223

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-350-4223

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.277 inches |
| Fastener Length: |
| Between 0.324 inches and 0.354 inches |
| Head Style: |
| Pan |
| Head Diameter: |
| Between 0.256 inches and 0.270 inches |
| Head Height: |
| Between 0.087 inches and 0.097 inches |
| Internal Drive Style: |
| Torque-set ribbed |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Hardness Rating: |
| Between 36.0 rockwell c and 40.0 rockwell c |
| Screw Material: |
| Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 |
| Screw Surface Treatment: |
| Cadmium and chromate |
| Screw Surface Treatment Specification: |
| Qq-p-416 ty2 cl2 federal specification single treatment response |
| Bearing Surface Of Head Surface Finish: |
| 32.0 microinches |
| Shank Surface Finish: |
| 32.0 microinches |
| Thread Surface Finish: |
| 32.0 microinches |
| Thread Series Designator: |
| Unjc |
| Specification Data: |
| 80205-nas1218 professional/industrial association standard |
| Shelf Life: |

N/a

NSN 5305-01-350-4223

Machine Screw - Page 2 of 2



| | | | ure: | |
|--|--|--|------|--|
| | | | | |
| | | | | |

--

Demilitarization:

No

Fiig:

A500d0