## NSN 5305-01-350-4223

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-350-4223

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.277 inches
Fastener Length:
Between 0.324 inches and 0.354 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.138 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150
Screw Surface Treatment:
Cadmium and chromate
Screw Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjc
Specification Data:
80205-nas1218 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-350-4223

Machine Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A500d0