NSN 5305-01-350-4553

Close Tolerance Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-350-4553

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.431 inches |
| Fastener Length: |
| Between 0.666 inches and 0.696 inches |
| Head Style: |
| Oval |
| Head Diameter: |
| Between 0.427 inches and 0.447 inches |
| Head Height: |
| Between 0.075 inches and 0.080 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1890 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 95000 pounds per square inch |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material: |
| Titanium alloy uns r56400 |
| Material Specification: |
| Ams 4928 assn standard single material response or ams 4967 assn standard single material response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |