

View Online at <https://aerobasegroup.com/nsn/5305-01-350-4554>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.235 inches and 0.280 inches

Fastener Length:

Between 0.922 inches and 0.952 inches

Head Style:

Pan

Head Diameter:

Between 0.350 inches and 0.380 inches

Head Height:

Between 0.095 inches and 0.125 inches

Internal Drive Style:

Slot

Material Accommodated Thickness:

Between 0.084 inches and 0.104 inches

Thread Diameter:

0.190 inches

Thread Qty Per Inch (tpi):

32

Color:

Black secondary washerblack primary washerblack stand-offblack fastener

Material:

Steel comp 303 secondary washersteel comp 302 primary washersteel comp 302 springsteel comp 304 stand-offsteel comp 302 fastener

Material Specification:

Mil-s-5059 military specification single material response first shoulderastm a493 assn standard single material response primary washerams 5688 assn standard single material response springqq-s-763 federal specification single material response stand-offastm a493 assn standard single material response fastener

Surface Treatment:

Oxide secondary washeroxide primary washerpassivate springoxide stand-offoxide fastener

Surface Treatment Specification:

Mil-c-13934 military specification single treatment response secondary washermil-c-13934 military specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-c-13934 military specification single treatment response stand-offmil-c-13934 military specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

Mil-std (military Standard):

Mil-s-5059 spec.