

View Online at <https://aerobasegroup.com/nsn/5305-01-350-4554>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.235 inches and 0.280 inches

**Fastener Length:**

Between 0.922 inches and 0.952 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.350 inches and 0.380 inches

**Head Height:**

Between 0.095 inches and 0.125 inches

**Internal Drive Style:**

Slot

**Material Accommodated Thickness:**

Between 0.084 inches and 0.104 inches

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Color:**

Black secondary washerblack primary washerblack stand-offblack fastener

**Material:**

Steel comp 303 secondary washersteel comp 302 primary washersteel comp 302 springsteel comp 304 stand-offsteel comp 302 fastener

**Material Specification:**

Mil-s-5059 military specification single material response first shoulderastm a493 assn standard single material response primary washerams 5688 assn standard single material response springqq-s-763 federal specification single material response stand-offastm a493 assn standard single material response fastener

**Surface Treatment:**

Oxide secondary washeroxide primary washerpassivate springoxide stand-offoxide fastener

**Surface Treatment Specification:**

Mil-c-13934 military specification single treatment response secondary washermil-c-13934 military specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-c-13934 military specification single treatment response stand-offmil-c-13934 military specification single treatment response fastener

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

**Mil-std (military Standard):**

Mil-s-5059 spec.