NSN 5305-01-351-0863

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-351-0863 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.277 inches **Fastener Length:** Between 0.450 inches and 0.480 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5731 assn standard single material response or am 5732 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches **Shank Surface Finish:** 32.0 microinches **Thread Surface Finish:** 32.0 microinches

Unjc

Specification Data:

Thread Series Designator:

80205-nas1218 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-351-0863

Machine Screw - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A500d0