

View Online at <https://aerobasegroup.com/nsn/5305-01-351-3514>

Thread Class:

3a

Thread Direction:

Left-hand

Thread Length:

Between 0.917 inches and 1.031 inches

Fastener Length:

Between 0.985 inches and 1.031 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.457 inches and 0.468 inches

Head Height:

Between 0.306 inches and 0.312 inches

Locking Feature:

Strip threads or pellet threads or patch threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.312 inches

Width Across Flats:

Between 0.250 inches and 0.253 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell c fastener

Minimum Yield Strength:

30000 pounds per square inch

Material:

Plastic polyamide locking feature steel comp 302 fastener or steel comp 304 fastener or steel comp 316 fastener or steel comp xm-7 fastener or steel comp 384 fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0