NSN 5305-01-351-3518



Shoulder Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-351-3518 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.500 inches **Fastener Length:** 2.375 inches **Head Style:** Flat chamfer **Head Diameter:** 0.750 inches **Head Height:** Between 0.370 inches and 0.380 inches **Shoulder Diameter:** 0.624 inches all shoulders and 0.625 inches all shoulders **Shoulder Length:** 1.875 inches all shoulders **Internal Drive Style:** Hexagon **Thread Diameter:** 0.500 inches Width Across Flats: Between 0.234 inches and 0.312 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 150000 pounds per square inch **Hardness Rating:** 32.0 rockwell c and 43.0 rockwell c **Shoulder Shape:** Round all shoulders Color: Black Material: Steel **Surface Treatment:** Phosphate manganese **Surface Treatment Specification:** Dod-p-16232 tym cl4 military specification single treatment response

Thread Series Designator:

Unf

NSN 5305-01-351-3518

Shoulder Screw - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
No Fiig:

Mil-std (military Standard):

spec.