NSN 5305-01-351-3522

За

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-351-3522

Thread Class:

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| 0.403 inches |
| Fastener Length: |
| Between 0.950 inches and 0.980 inches |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 0.350 inches and 0.399 inches |
| Grip Diameter: |
| Between 0.2490 inches and 0.2495 inches |
| Internal Drive Style: |
| Offset cruciform (torque set) |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.552 inches and 0.572 inches |
| Thready Qty Per Inch (tpi): |
| 28 |
| Min. Tensile Strength (psi): |
| 220000 pounds per square inch |
| Countersink Angle: |
| Between 99.0 degrees and 101.0 degrees |
| Surface Finish: |
| 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads |
| Material: |
| Nickel alloy 718 |
| Material Specification: |
| Ams 5662 assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 5305-01-351-3522

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0