## NSN 5305-01-351-3588

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-351-3588 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** Between 2.515 inches and 2.547 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.447 inches and 0.507 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Hardness Rating:** Between 26.0 rockwell c and 32.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 8740 or steel comp 8630 **Screw Material Specification:** Mil-s-6049 military specification 1st material response or mil-s-6050 military specification 2nd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Special Features:** Shank hole 0.077 to 0.082 dia, 1.200 in from top of head to hole **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A500d0

## NSN 5305-01-351-3588

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-6049 spec.