

View Online at <https://aerobasegroup.com/nsn/5305-01-351-5118>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.252 inches

Fastener Length:

1.530 inches

Head Style:

Flat countersunk

Head Diameter:

0.540 inches

First Diameter From Head:

Between 0.4065 inches and 0.4075 inches

Second Diameter From Head:

Between 0.187 inches and 0.197 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

1.060 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.207 inches

Internal Drive Style:

Slot

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

180000 pounds per square inch

Countersink Angle:

100.0 degrees

Externally Relieved Body Diameter Quantity:

2

Material:

Steel comp e4340

Material Specification:

Mil-s-5000, cond. C4 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Mil-c-8837, ty2 cl2 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.