NSN 5305-01-351-5118

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-351-5118 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.252 inches **Fastener Length:** 1.530 inches **Head Style:** Flat countersunk **Head Diameter:** 0.540 inches **First Diameter From Head:** Between 0.4065 inches and 0.4075 inches **Second Diameter From Head:** Between 0.187 inches and 0.197 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.060 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.207 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** 100.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp e4340 **Material Specification:** Mil-s-5000, cond. C4 military specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Mil-c-8837, ty2 cl2 military specification single treatment response

Unjf

Thread Series Designator:

NSN 5305-01-351-5118

Externally Relieved Body Screw - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Mil-s-5000 spec.

Shelf Life: