## NSN 5305-01-351-7082

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-351-7082 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.251 inches and 0.301 inches **Fastener Length:** Between 2.011 inches and 2.041 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.306 inches and 0.313 inches **Head Height:** Between 0.103 inches and 0.118 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.740 inches and 1.760 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1123 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

No

## NSN 5305-01-351-7082

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0