NSN 5305-01-352-1148

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-352-1148 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.175 inches and 0.185 inches **Fastener Length:** Between 0.550 inches and 0.570 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** 0.130 inches **First Diameter From Head:** Between 0.067 inches and 0.072 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.365 inches and 0.395 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.094 inches and 0.095 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, ty2, cl3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-352-1148

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0