

View Online at <https://aerobasegroup.com/nsn/5305-01-352-1217>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.360 inches and 0.390 inches

Fastener Length:

Between 0.547 inches and 0.577 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.365 inches and 0.395 inches

Head Height:

Between 0.244 inches and 0.250 inches

Internal Drive Style:

Hexagon

Material Accommodated Thickness:

0.070 inches

Thread Diameter:

0.250 inches

Width Across Flats:

0.187 inches

Thready Qty Per Inch (tpi):

28

Color:

Black

Material:

Steel comp 302 secondary washer or steel comp 302b secondary washer or steel comp 303 secondary washer or steel comp 303 plus x secondary washer or steel comp 303se secondary washer or steel comp 303cu secondary washer or steel comp 303ma secondary washer or steel comp 303pb secondary washer or steel comp 304 secondary washer or steel comp 304l secondary washer steel comp 302 primary washer steel comp 302 spring steel comp 302 stand-off or steel comp 302b stand-off or steel comp 303 stand-off or steel comp 303 plus x stand-off or steel comp 303se stand-off or steel comp 303cu stand-off or steel comp 303ma stand-off or steel comp 303pb stand-off or steel comp 304 stand-off or steel comp 304l stand-off steel comp 302 fastener or steel comp 302b fastener or steel comp 303 fastener or steel comp 303 plus x fastener or steel comp 303se fastener or steel comp 303cu fastener or steel comp 303ma fastener or steel comp 303pb fastener or steel comp 304 fastener or steel comp 304l fastener

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 military specification single treatment response

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Mil-std (military Standard):

Mil-c-13924 spec.