

View Online at <https://aerobasegroup.com/nsn/5305-01-352-2074>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.594 inches

Fastener Length:

Between 0.829 inches and 0.859 inches

Head Style:

Pan

Head Diameter:

Between 0.722 inches and 0.740 inches

Head Height:

Between 0.206 inches and 0.220 inches

Grip Diameter:

Between 0.3735 inches and 0.3745 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.375 inches

Grip Length:

Between 0.240 inches and 0.260 inches

Thread Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1578 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.