

View Online at <https://aerobasegroup.com/nsn/5305-01-352-3297>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.312 inches and 0.333 inches

Fastener Length:

Between 0.844 inches and 0.875 inches

Head Style:

Pan

Head Diameter:

Between 0.357 inches and 0.373 inches

Head Height:

Between 0.122 inches and 0.133 inches

First Diameter From Head:

Between 0.133 inches and 0.143 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.511 inches and 0.563 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

24

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924 cl4 military specification single treatment response

Thread Series Designator:

Unc

Specification Or Standard:

3 type and 9c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.