## NSN 5305-01-352-8141

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-352-8141 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.448 inches **Fastener Length:** Between 1.433 inches and 1.463 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.578 inches and 0.634 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 260000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads Material: Cobalt comp mp-35-n **Material Specification:** Ams 5844 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

**Unit Of Measure:** 

## NSN 5305-01-352-8141

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0