

View Online at <https://aerobasegroup.com/nsn/5305-01-352-8883>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.182 inches and 0.192 inches

Fastener Length:

0.605 inches

Head Style:

Knurled no. 1

Head Diameter:

0.356 inches

Head Height:

0.385 inches

Internal Drive Style:

Cross recess type 1

Material Accommodated Thickness:

Between 0.032 inches and 0.093 inches

Thread Diameter:

0.138 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Material:

Aluminum alloy 6061 headsteel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offsteel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 321 fastener or steel comp 347 fastener or steel comp 384 fastener

Material Specification:

Qq-a-225/8 federal specification single material response headmil-s-5059a military specification single material response primary washerastm a580 assn standard single material response springqq-a-225/8 federal specification single material response stand-offastm a493 assn standard all material responses fastener

Surface Treatment:

Anodize headpassivate primary washerpassivate springanodize stand-offpassivate fastener

Surface Treatment Specification:

Mil-a-8625, cl1, ty1 military specification single treatment response headqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625, ty1, cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Mil-std (military Standard):

Mil-s-5059a spec.