NSN 5305-01-353-0293

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-353-0293 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.379 inches and 1.750 inches **Fastener Length:** Between 1.690 inches and 1.750 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.921 inches and 0.937 inches **Head Height:** Between 0.616 inches and 0.625 inches **Locking Feature:** Strip threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.625 inches Width Across Flats: Between 0.500 inches and 0.505 inches Thready Qty Per Inch (tpi): 18 Min. Tensile Strength (psi): 170000 pounds per square inch **Hardness Rating:** 38.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 150000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416, type 2 cl 2 federal specification single treatment response **Thread Series Designator:**

Unrf
Shelf Life:
N/a
Unit Of Measure:
--

NSN 5305-01-353-0293

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0