
Socket Head Cap Screw - Page 1 of 2





3aThread Direction:Right-handThread Length:Between 1.379 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.921 inches and 0.937 inchesHead Height:Between 0.616 inches and 0.625 inchesLocking Feature:Strip threadsInternal Drive Style:HexagonChread Diameter:0.625 inchesWidth Across Flats:
Right-handThread Length:Between 1.379 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.921 inches and 0.937 inchesHead Height:Between 0.616 inches and 0.625 inchesLocking Feature:Strip threadsInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:
Thread Length:Between 1.379 inches and 1.750 inchesFastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.921 inches and 0.937 inchesHead Height:Between 0.616 inches and 0.625 inchesLocking Feature:Strip threadsInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:
Between 1.379 inches and 1.750 inches Fastener Length: Between 1.690 inches and 1.750 inches Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.937 inches Head Height: Between 0.616 inches and 0.625 inches Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Fastener Length:Between 1.690 inches and 1.750 inchesHead Style:Flat chamferHead Diameter:Between 0.921 inches and 0.937 inchesHead Height:Between 0.616 inches and 0.625 inchesLocking Feature:Strip threadsInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:
Between 1.690 inches and 1.750 inches Head Style: Flat chamfer Head Diameter: Between 0.921 inches and 0.937 inches Head Height: Between 0.616 inches and 0.625 inches Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Head Style:Flat chamferHead Diameter:Between 0.921 inches and 0.937 inchesHead Height:Between 0.616 inches and 0.625 inchesLocking Feature:Strip threadsInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:
Flat chamfer Head Diameter: Between 0.921 inches and 0.937 inches Head Height: Between 0.616 inches and 0.625 inches Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Head Diameter:Between 0.921 inches and 0.937 inchesHead Height:Between 0.616 inches and 0.625 inchesLocking Feature:Strip threadsInternal Drive Style:HexagonThread Diameter:0.625 inchesWidth Across Flats:
Between 0.921 inches and 0.937 inches Head Height: Between 0.616 inches and 0.625 inches Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Head Height: Between 0.616 inches and 0.625 inches Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Between 0.616 inches and 0.625 inches Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Locking Feature: Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Strip threads Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Internal Drive Style: Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Hexagon Thread Diameter: 0.625 inches Width Across Flats:
Thread Diameter: 0.625 inches Width Across Flats:
0.625 inches Width Across Flats:
Width Across Flats:
Between 0.500 inches and 0.505 inches
Thready Qty Per Inch (tpi):
18
Min. Tensile Strength (psi):
170000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Minimum Yield Strength:
150000 pounds per square inch
Material:
Steel
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unrf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-353-0293

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

