## NSN 5305-01-353-1868



Panel Screw Assembly - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-353-1868 **Thread Class:** За **Thread Direction:** Right-hand **Fastener Length:** 1.120 inches **Head Style:** Knurled no. 1 **Head Diameter:** 0.451 inches **Head Height:** 0.520 inches **Internal Drive Style:** Hexagon **Material Accommodated Thickness:** Between 0.156 inches and 0.217 inches **Thread Diameter:** 0.250 inches Width Across Flats: 0.156 inches Thready Qty Per Inch (tpi): 20 Material: Aluminum alloy 6061 headsteel comp 301 secondary washersteel comp 301 primary washersteel comp 302 springaluminum alloy 6061 stand-offstainless steel fastener **Material Specification:** Qq-a-225/8 federal specification single material response headmil-s-5059 military specification single material response secondary washermil-s-5059 military specification single material response primary washerqq-w-423 federal specification single material response springgq-a-225/8 federal specification single material response stand-offastm a493 300 series assn standard single material response fastener **Surface Treatment:** Anodize headpassivate secondary washerpassivate primary washerpassivate springanodize stand-offpassivate fastener **Surface Treatment Specification:** Mil-a-8625 ty1 cl1 military specification single treatment response headgg-p-35 federal specification single treatment response secondary washerqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springmil-a-8625 ty1 cl1 military specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unc

Demilitarization:

**Unit Of Measure:** 

Shelf Life:

N/a