

View Online at <https://aerobasegroup.com/nsn/5305-01-353-1885>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

0.750 inches

Head Style:

Hexagon

Head Height:

Between 0.125 inches and 0.140 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

Internal Drive Style:

W/o internal drive

Thread Diameter:

0.250 inches

Thready Qty Per Inch (tpi):

28

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

Screw Surface Treatment:

Passivate

Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Special Features:

Keyway, chamfered dog point 0.100 in. Lg. 0.202 maximum dia

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0