

View Online at <https://aerobasegroup.com/nsn/5305-01-353-2565>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.162 inches and 0.226 inches

Fastener Length:

Between 0.220 inches and 0.250 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.130 inches and 0.149 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.073 inches

Thready Qty Per Inch (tpi):

72

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Navy special project

Screw Material:

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 385

Screw Surface Treatment:

Oxide

Screw Surface Treatment Specification:

Mil-c-13924 cl4 military specification single treatment response

Color:

Black

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-c-13924 spec.