## NSN 5305-01-353-3629

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-353-3629

| Thread Class:  |
|--|
|  |
| 3a<br>Thursed Dissetters   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.276 inches   |
| Fastener Length:   |
| Between 1.199 inches and 1.229 inches  |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| Between 0.246 inches and 0.280 inches  |
| Grip Diameter:   |
| Between 0.1370 inches and 0.1375 inches  |
| Internal Drive Style:  |
| Cross recess type 1  |
| Thread Diameter:   |
| 0.138 inches   |
| Grip Length:   |
| Between 0.928 inches and 0.938 inches  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Countersink Angle:   |
| Between 99.0 degrees and 101.0 degrees   |
| Material:  |
| Iron alloy 660   |
| Material Specification:  |
| Ams5731 assn standard single material response or ams5737 assn standard single material response |
| Surface Treatment:   |
| Passivate  |
| Surface Treatment Specification:   |
| Qq-p-35 federal specification single treatment response  |
| Thread Series Designator:  |
| Unjc   |
| Specification Data:  |
| 80205-nas7501 professional/industrial association standard                                       |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| Νο   |

## NSN 5305-01-353-3629

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

