NSN 5305-01-353-3718

Machine Screw - Page 1 of 2

Thread Class:

View Online at https://aerobasegroup.com/nsn/5305-01-353-3718



3a **Thread Direction: Right-hand Thread Length:** Between 0.245 inches and 0.312 inches Fastener Length: Between 0.281 inches and 0.312 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.136 inches and 0.140 inches **Head Height:** Between 0.044 inches and 0.053 inches Locking Feature: Strip **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.086 inches Thready Qty Per Inch (tpi): 56 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Stainless steel Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Bearing Surface Of Head Surface Finish:** 32.0 microinches Shank Surface Finish: 32.0 microinches **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjc

NSN 5305-01-353-3718

Machine Screw - Page 2 of 2



Specification Data:

80205-nas1191 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0