

View Online at <https://aerobasegroup.com/nsn/5305-01-353-3719>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.528 inches and 0.620 inches

**Fastener Length:**

Between 0.590 inches and 0.620 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.080 inches and 0.093 inches

**Width Between Flats:**

Between 0.244 inches and 0.250 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Screw Material:**

Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385

**Screw Material Specification:**

Ff-s-92 federal specification single material response

**Screw Surface Treatment:**

Passivate

**Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and a style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A500d0