NSN 5305-01-353-8320

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-353-8320 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.275 inches **Fastener Length:** 0.625 inches **Head Style:** Hexagon **Head Height:** Between 0.096 inches and 0.110 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Internal Drive Style:** Err-090 **Thread Diameter:** 0.164 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Screw Material:** Iron alloy 660 **Screw Material Specification:** Ams 5732 assn standard single material response or ams 5736 assn standard single material response or ams 5737 assn standard single material response **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Furnished with keyway in threads also split retaining ring cres and passivate **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-353-8320

Machine Screw - Page 2 of 2



Fiig:

A500d0