# NSN 5305-01-353-8990

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-353-8990

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Fastener Length:

0.614 inches

## Head Style:

Flat chamfer

#### Head Diameter:

0.451 inches

Head Height:

0.520 inches

Internal Drive Style:

Slot

#### Material Accommodated Thickness:

Between 0.032 inches and 0.093 inches

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

**Special Features:** 

Furnished with nut plate

### Material:

Aluminum alloy 6061 headsteel comp 301 secondary washersteel comp 631 primary washersteel comp 302 springsteel comp 304 stand-offsteel comp 303 fastener

#### **Material Specification:**

Qq-a-225/8 federal specification single material response headmil-s-5059 military specification single material response secondary washermil-s-25043 military specification single material response primary washerastm a580 assn standard single material response springqq-s-763 federal specification single material response stand-offastm a493 assn standard single material response fastener

## Surface Treatment:

Anodize headpassivate secondary washerpassivate primary washerpassivate springpassivate stand-offpassivate fastener

# Surface Treatment Specification:

Mil-a-8625, ty1, cl1 military specification single treatment response headqq-p-35 federal specification single treatment response secondary washerqq-p-35 federal specification single treatment response primary washerqq-p-35 federal specification single treatment response springqq-p-35 federal specification single treatment response stand-offqq-p-35 federal specification single treatment response fastener

# Thread Series Designator:

Unf

Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

Fiig: