## NSN 5305-01-354-1915

Machine Screw - Page 1 of 1

AeroBase Group

response or mil-s-6049 military

View Online at https://aerobasegroup.com/nsn/5305-01-354-1915

Thre	ad Class:
3a	
Thre	ad Direction:
Righ	t-hand
Thre	ad Length:
0.57	9 inches
Fast	ener Length:
Betw	reen 1.814 inches and 1.844 inches
Head	d Style:
Flat	countersunk
Head	d Diameter:
Betw	een 0.703 inches and 0.762 inches
Inter	nal Drive Style:
High	-torque
Thre	ad Diameter:
0.37	5 inches
Thre	ady Qty Per Inch (tpi):
24	
Min.	Tensile Strength (psi):
1600	00 pounds per square inch
Cou	ntersink Angle:
Betw	veen 99.0 degrees and 101.0 degrees
Scre	w Material:
Stee	l comp 4140 or steel comp e4340 or steel comp 8740
Scre	w Material Specification:
Mil-s	-5626 military specification 1st material response or mil-s-5000 military specification 2nd material i
spec	ification 3rd material response
Scre	w Surface Treatment:
Cadı	nium and chromate
Scre	w Surface Treatment Specification:
Qq-p	-416 type 2 class 2 federal specification single treatment response
Thre	ad Series Designator:
Unjf	
She	f Life:
N/a	
Unit	Of Measure:
Dem	ilitarization:
No	
Fiig:	
A500	Dd0
Mil-s	atd (military Standard):
	-5626 spec.