NSN 5305-01-354-2465

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-2465 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.687 inches **Head Style:** Pan **Head Diameter:** Between 0.391 inches and 0.403 inches **Head Height:** Between 0.126 inches and 0.133 inches **First Diameter From Head:** Between 0.140 inches and 0.145 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.312 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches **Features Provided:** O ring Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Special Features:** W/one fluorosilicone o-ring per mil-r-25988 Steel comp 302 or steel comp 304 or steel comp 305 **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-c-13924 cl2 military specification single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-354-2465

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.