

View Online at <https://aerobasegroup.com/nsn/5305-01-354-2465>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.375 inches

**Fastener Length:**

0.687 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.391 inches and 0.403 inches

**Head Height:**

Between 0.126 inches and 0.133 inches

**First Diameter From Head:**

Between 0.140 inches and 0.145 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

0.312 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.190 inches

**Features Provided:**

O ring

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

W/one fluorosilicone o-ring per mil-r-25988

**Material:**

Steel comp 302 or steel comp 304 or steel comp 305

**Surface Treatment:**

Oxide

**Surface Treatment Specification:**

Mil-c-13924 cl2 military specification single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.