Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-2466

| 2a | Class: |
|----------------------|--|
| | |
| Thread D | Direction: |
| Right-har | nd |
| Thread L | ength: |
| 0.250 inc | hes |
| Fastener | Length: |
| Between | 1.313 inches and 1.375 inches |
| Head Sty | /le: |
| Pan | |
| Head Dia | ameter: |
| Between | 0.205 inches and 0.219 inches |
| Head He | ight: |
| Between | 0.070 inches and 0.080 inches |
| First Dia | meter From Head: |
| Between | 0.075 inches and 0.085 inches |
| Distance | From Largest Bearing Surface Of Head To End Of First Diameter: |
| 1.125 inc | hes |
| Internal I | Drive Style: |
| Cross rec | cess type 1 |
| Thread D | Diameter: |
| 0.112 inc | hes |
| Thready | Qty Per Inch (tpi): |
| 40 | |
| External | ly Relieved Body Diameter Quantity: |
| 1 | |
| Material: | |
| Stainless | steel |
| Material | Specification: |
| Qq-s-763 | 300 ser. Federal specification single material response or fed66 300 ser. Federal standard single material respons |
| Surface ⁻ | Treatment: |
| Passivate | |
| Surface ⁻ | Treatment Specification: |
| Qq-p-35 f | federal specification single treatment response |
| Thread S | Series Designator: |
| Unc | |
| Shelf Life | e: |
| N/a | |
| | leasure: |

NSN 5305-01-354-2466

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

