

View Online at <https://aerobasegroup.com/nsn/5305-01-354-2495>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.276 inches

Fastener Length:

Between 0.449 inches and 0.479 inches

Head Style:

Pan

Head Diameter:

Between 0.256 inches and 0.270 inches

Head Height:

Between 0.087 inches and 0.097 inches

Grip Diameter:

Between 0.1365 inches and 0.1375 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.138 inches

Grip Length:

Between 0.178 inches and 0.198 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Surface Finish:

63.0 microinches bearing surface of head32.0 microinches grip32.0 microinches threads

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response or ams6322 assn standard
2nd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 ty2 cl2 federal specification single treatment response

Thread Series Designator:

Unjc

Specification Data:

80205-nas7701 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.