## NSN 5305-01-354-2840

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-354-2840 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 2.076 inches and 2.232 inches **Fastener Length:** Between 2.218 inches and 2.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.322 inches and 0.385 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Steel comp 4140 or steel comp e4340 or steel comp 8740 **Screw Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Mil-s-5626 spec.

Mil-std (military Standard):

Fiig: A500d0