NSN 5305-01-354-2841

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-354-2841



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.796 inches and 1.911 inches Fastener Length: Between 1.858 inches and 1.911 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.322 inches and 0.385 inches Locking Feature: Patch or pellet or strip **Internal Drive Style:** Torque set **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Screw Material:** Iron alloy 660 Locking Feature Material: Plastic polyamide **Screw Material Specification:** Ams5737 assn standard single material response **Screw Surface Treatment:** Passivate **Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Surface Finish:** 32.0 microinches **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1189 professional/industrial association standard Shelf Life:

N/a

NSN 5305-01-354-2841

Machine Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A500d0

