NSN 5305-01-354-4231

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-354-4231 **Thread Class:**

За

Thread Direction:

Right-hand

Thread Length:

Between 0.333 inches and 0.375 inches

Fastener Length:

0.375 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.176 inches and 0.183 inches

Head Height:

Between 0.108 inches and 0.112 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.112 inches

Width Across Flats:

Between 0.093 inches and 0.095 inches

Thready Qty Per Inch (tpi):

48

Min. Tensile Strength (psi):

180000 pounds per square inch

Hardness Rating:

38.0 rockwell c fastener and 45.0 rockwell c fastener

Minimum Yield Strength:

155000 pounds per square inch

Material:

Plastic polyamide locking featuresteel fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416ty2cl2 federal specification single treatment response fastener

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

NSN 5305-01-354-4231

Socket Head Cap Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0